

# TULA nano suspended

canopy surface


049-571051XM 005-2602137



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Suspended \_\_\_\_\_

special colours \_\_\_\_\_

Canopy traffic white \_\_\_\_\_

IP20 \_\_\_\_\_

744 lm \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

CRI  $\geq$  90 \_\_\_\_\_

initial MacAdam  $\leq$  3 SDCM \_\_\_\_\_

## Optical

medium \_\_\_\_\_

beam angle 25° \_\_\_\_\_

## Electrical

DALI-2 \_\_\_\_\_

12.1 W \_\_\_\_\_

PC2 220-240V \_\_\_\_\_

61 lm/W \_\_\_\_\_


## Physical

diameter 26 mm \_\_\_\_\_

height 500 mm \_\_\_\_\_

Decorative suspended luminaire in aluminium; surface special colours powder coated; pendant fitting with 1500mm suspension; incl. feed (white), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam  $\leq$  3 SDCM; CRI  $\geq$  90; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;

## Light distribution



medium 25°

h (m)	EO° (lx)	ø (m)
1	2790	0.44
2	700	0.89
3	310	1.33
4	170	1.77
5	110	2.22

## Product drawing



## Installation instructions



## Lighting calculator



# TULA nano suspended

canopy surface

049-571051XM 005-2602137



Project / Type

Notes

Count / Date

## Components

### CANOPY

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
500 mA   DALI-2	traffic white	115	005-2602137



## Mounting accessories

### SPECIAL MOUNTING TOOL

TYPE	Ø (MM)	ARTICLE NUMBER(S)
necessary to install mounting housing trimless	100	063-8912110



### RING CEILING MOUNTED

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	50	050-0510217
jet black	50	050-0510218



### HOOK

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
traffic white	18-13-58	050-5901117
jet black	18-13-58	050-5901118



## Optional electrical accessories

### DIN RAIL POWER SUPPLY

L-W-H (MM)	ARTICLE NUMBER(S)
72-90-63	005-6520210



### DIN RAIL LED DRIVER

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
DALI-2   200-1050 mA   2 x 42W	36-88-59	005-6121030

