

# TULA nano suspended

canopy surface

049-5510417M 005-2602197



Project / Type

Notes

Count / Date



## General

Ceiling , Suspended

white , RAL9016 <sup>1</sup>

Canopy traffic white

IP20

699 lm

## LED

2700 K

CRI ≥ 90

initial MacAdam ≤ 3 SDCM

## Optical

medium

beam angle 25°

## Electrical

Casambi

12.0 W

PC2 220-240V

58 lm/W

## Physical

diameter 26 mm

height 300 mm

Decorative suspended luminaire in aluminium; surface white powder coated; pendant fitting with 1500mm suspension; incl. feed (white), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;

<sup>1</sup> RAL code


## Light distribution



medium 25°

| h (m) | EO° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 2620     | 0.44  |
| 2     | 660      | 0.89  |
| 3     | 290      | 1.33  |
| 4     | 160      | 1.77  |
| 5     | 100      | 2.22  |

## Product drawing



## Installation instructions



## Lighting calculator

