

BO 32 semi-recessed

049-6120418M 002-90743



Project / Type

Notes

Count / Date



| |
|------------------------------|
| General |
| Ceiling , Semi-Recessed |
| tilt max 90° |
| rotation 350° |
| black , RAL9005 ¹ |
| IP20 |
| 786 lm |

| |
|--|
| LED |
| 2700 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 99 , R _f : 91 , R ₍₁₋₁₅₎ : 89 |
| MR 0.53 |
| MDER 0.48 |

| |
|--------------------------|
| Optical |
| medium |
| beam angle 24° |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Cylindrical spotlight in aluminium; surface black powder coated; 350° rotatable and 90° tiltable; recessed version with trim; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 24° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC2 220-240V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



| | | | |
|------------|----------|-------|--|
| medium 24° | | | |
| h (m) | EO° (lx) | ø (m) | |
| 1 | 4180 | 0.42 | |
| 2 | 1040 | 0.83 | |
| 3 | 460 | 1.25 | |
| 4 | 260 | 1.67 | |
| 5 | 170 | 2.09 | |

Product drawing



| |
|--------------|
| Electrical |
| DALI-2 |
| 11.6 W |
| PC2 220-240V |
| 68 lm/W |
| 1 DALI Addr. |

| |
|----------------|
| Physical |
| diameter 32 mm |
| height 139 mm |
| 0.4 kg |

| |
|------------------------------|
| Cutout |
| min. ceiling thickness 2 mm |
| max. ceiling thickness 25 mm |
| recessed depth 110 mm |

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

