

# TULA nano suspended

canopy surface

049-5710518F 005-2602138



Project / Type

Notes

Count / Date



### General

Ceiling , Suspended

black , RAL9005 <sup>1</sup>

Canopy jet black

IP20

717 lm

### LED

3000 K

CRI ≥ 90

initial MacAdam ≤ 3 SDCM

### Optical

flood

beam angle 30°

### Electrical

DALI-2

12.1 W

PC2 220-240V

59 lm/W

### Physical


diameter 26 mm

height 500 mm

Decorative suspended luminaire in aluminium; surface black powder coated; pendant fitting with 1500mm suspension; incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 30° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;

<sup>1</sup> RAL code

### Light distribution



flood 30°

h (m)	EO° (lx)	ø (m)
1	2110	0.53
2	530	1.07
3	230	1.60
4	130	2.13
5	80	2.66

### Product drawing



### Installation instructions



### Lighting calculator

