

ARY adjustable rod suspended canopy surface

049-5231418M 005-2602138



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____
 tilt max 90° _____
 rotation 265° _____
 black , RAL9005 ¹ _____
 Canopy jet black _____
 IP20 _____
 642 lm _____

LED

2700 K _____
 CRI ≥ 90 _____
 L90 / 50000 h _____
 initial MacAdam ≤ 3 SDCM _____
 R_g: 99 , R_r: 91 , R₍₁₋₁₅₎: 89 _____
 MR 0.54 _____
 MDER 0.49 _____

Optical

medium _____
 beam angle 25° _____

Electrical

DALI-2 _____
 11.2 W _____
 PC2 220-240V _____
 57 lm/W _____
 1 DALI Addr. _____

Physical

rod 1500 mm with hook _____
 diameter 47 mm _____
 height 110 mm _____
 0.5 kg _____

¹ RAL code

Installation instructions




Lighting calculator



Decorative suspended luminaire in aluminium; surface black powder coated; height adjustable U-profile pendant rod suspension (black) 1500mm, feed 2000mm (1500mm in U-profile), incl. ceiling mounting ring + hook (black) for multiple positioning of the luminaire in the room; spotlight head 265° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	2780	0.44
2	690	0.89
3	310	1.33
4	170	1.78
5	110	2.22

Product drawing

