

# TULA nano suspended

canopy surface

049-5710514M 005-2602198



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Suspended \_\_\_\_\_

chrome \_\_\_\_\_

Canopy jet black \_\_\_\_\_

IP20 \_\_\_\_\_

744 lm \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

CRI  $\geq$  90 \_\_\_\_\_

initial MacAdam  $\leq$  3 SDCM \_\_\_\_\_

## Optical

medium \_\_\_\_\_

beam angle 25° \_\_\_\_\_

## Electrical

Casambi \_\_\_\_\_

12.1 W \_\_\_\_\_

PC2 220-240V \_\_\_\_\_

61 lm/W \_\_\_\_\_

## Physical


diameter 26 mm \_\_\_\_\_

height 500 mm \_\_\_\_\_

0.25 kg \_\_\_\_\_

Decorative suspended luminaire in aluminium; surface polished chrome; pendant fitting with 1500mm suspension; incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam  $\leq$  3 SDCM; CRI  $\geq$  90; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;

## Light distribution



medium 25°

h (m)	EO° (lx)	ø (m)
1	2790	0.44
2	700	0.89
3	310	1.33
4	170	1.77
5	110	2.22

## Product drawing



## Installation instructions



## Lighting calculator

