

# ARY rod suspended

canopy trimless

049-5221618M 005-3511017 002-90732



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Suspended  
 black , RAL9005 <sup>1</sup>  
 Canopy traffic white  
 IP20  
 739 lm

## LED

4000 K  
 CRI ≥ 90  
 L90 / 50000 h  
 initial MacAdam ≤ 3 SDCM  
 R<sub>g</sub>: 99 , R<sub>r</sub>: 89 , R<sub>(1-15)</sub>: 87  
 MR 0.81  
 MDER 0.73

## Optical

medium  
 beam angle 25°  
 PstLM ≤ 1.0 <sup>2</sup>  
 SVM ≤ 0.4 <sup>2</sup>

## Electrical

non DIM  
 11.2 W  
 PC2 220-240V  
 66 lm/W

## Physical

rod 1500 mm with hook  
 diameter 47 mm  
 height 110 mm  
 0.64 kg


## Cutout

diameter 65 mm  
 min. ceiling thickness 9 mm  
 max. ceiling thickness 25 mm  
 recessed depth 70 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

Decorative suspended luminaire in aluminium; surface black powder coated; height adjustable U-profile pendant rod suspension (black) 1500mm, feed 2000mm (1500mm in U-profile), incl. ceiling mounting ring + hook (black) for multiple positioning of the luminaire in the room; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; canopy for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 9-25 mm; special mounting tool for easy installation of the trimless housing available as an accessory; incl. converter, non dimmable; external converter for ceiling insertion; light source not replaceable; control gear replaceable by an authorized professional;


## Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

## Product drawing



## Installation instructions



## Lighting calculator

