

TULA nano suspended

canopy surface

049-5510517F 005-2602197



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

white , RAL9016 ¹

Canopy traffic white

IP20

717 lm

LED

3000 K

CRI ≥ 90

initial MacAdam ≤ 3 SDCM

Optical

flood

beam angle 30°

Electrical

Casambi

12.1 W

PC2 220-240V

59 lm/W

Physical


diameter 26 mm

height 300 mm

Decorative suspended luminaire in aluminium; surface white powder coated; pendant fitting with 1500mm suspension; incl. feed (white), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 30° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;

¹ RAL code


Light distribution



flood 30°

| h (m) | EO° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 2110 | 0.53 |
| 2 | 530 | 1.07 |
| 3 | 230 | 1.60 |
| 4 | 130 | 2.13 |
| 5 | 80 | 2.66 |

Product drawing



Installation instructions



Lighting calculator



TULA nano suspended

canopy surface

049-5510517F 005-2602197



Project / Type

Notes

Count / Date

Components

CANOPY

| TYPE | COLOUR | Ø (MM) | ARTICLE NUMBER(S) |
|------------------|---------------|--------|-------------------|
| 500 mA Casambi | traffic white | 115 | 005-2602197 |



Mounting accessories

SPECIAL MOUNTING TOOL

| TYPE | Ø (MM) | ARTICLE NUMBER(S) |
|--|--------|-------------------|
| necessary to install mounting housing trimless | 100 | 063-8912110 |



RING CEILING MOUNTED

| COLOUR | Ø (MM) | ARTICLE NUMBER(S) |
|---------------|--------|-------------------|
| traffic white | 50 | 050-0510217 |
| jet black | 50 | 050-0510218 |



HOOK

| COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|---------------|------------|-------------------|
| traffic white | 18-13-58 | 050-5901117 |
| jet black | 18-13-58 | 050-5901118 |



Optional electrical accessories

DIN RAIL POWER SUPPLY

| L-W-H (MM) | ARTICLE NUMBER(S) |
|------------|-------------------|
| 72-90-63 | 005-6520210 |



DIN RAIL LED DRIVER

| TYPE | L-W-H (MM) | ARTICLE NUMBER(S) |
|--------------------------------|------------|-------------------|
| DALI-2 200-1050 mA 2 x 42W | 36-88-59 | 005-6121030 |

