

ARY adjustable rod suspended

canopy trim

049-5231517M 005-3521017 002-90733



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____
 tilt max 90° _____
 rotation 265° _____
 white , RAL9016 ¹ _____
 Canopy traffic white _____
 IP20 _____
 739 lm _____

LED

3000 K _____
 CRI ≥ 90 _____
 L90 / 50000 h _____
 initial MacAdam ≤ 3 SDCM _____
 R_g: 100 , R_r: 90 , R₍₁₋₁₅₎: 87 _____
 MR 0.59 _____
 MDER 0.54 _____

Optical

medium _____
 beam angle 25° _____
 P_{stLM} ≤ 1.0 ² _____
 SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____
 11.2 W _____
 PC2 220-240V _____
 66 lm/W _____
 1 DALI Addr. _____

Physical


rod 1500 mm with hook _____
 diameter 47 mm _____
 height 110 mm _____
 0.7 kg _____

Cutout

diameter 65 mm _____
 min. ceiling thickness 2 mm _____
 max. ceiling thickness 25 mm _____
 recessed depth 130 mm _____

¹ RAL code ² Value of containing product at full load (undimmed)



Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

Product drawing



Installation instructions



Lighting calculator

