

# ARY rod suspended canopy surface

049-5221517F 005-2602117



Project / Type \_\_\_\_\_  
 Notes \_\_\_\_\_  
 Count / Date \_\_\_\_\_



## General

Ceiling , Suspended \_\_\_\_\_  
 white , RAL9016 <sup>1</sup> \_\_\_\_\_  
 Canopy traffic white \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 791 lm \_\_\_\_\_

## LED

3000 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 L90 / 50000 h \_\_\_\_\_  
 initial MacAdam ≤ 3 SDCM \_\_\_\_\_  
 R<sub>g</sub>: 100 , R<sub>f</sub>: 90 , R<sub>(f-15)</sub>: 87 \_\_\_\_\_  
 MR 0.59 \_\_\_\_\_  
 MDER 0.54 \_\_\_\_\_

## Optical

flood \_\_\_\_\_  
 beam angle 44° \_\_\_\_\_

## Electrical


non DIM \_\_\_\_\_  
 11.2 W \_\_\_\_\_  
 PC2 220-240V \_\_\_\_\_  
 71 lm/W \_\_\_\_\_

## Physical

rod 1500 mm with hook \_\_\_\_\_  
 diameter 47 mm \_\_\_\_\_  
 height 110 mm \_\_\_\_\_  
 0.5 kg \_\_\_\_\_

Decorative suspended luminaire in aluminium; surface white powder coated; height adjustable U-profile pendant rod suspension (white) 1500mm, feed 2000mm (1500mm in U-profile), incl. ceiling mounting ring + hook (white) for multiple positioning of the luminaire in the room; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;


## Light distribution



flood 44°

h (m)	E0° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

## Product drawing



<sup>1</sup> RAL code

## Installation instructions



## Lighting calculator



[049-5221517F 005-2602117] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

25.05.2024

1 / 1