

ARY rod suspended

canopy trimless

049-512141XM 005-3512017 002-90733



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____
 special colours _____
 Canopy traffic white _____
 IP20 _____
 642 lm _____

LED

2700 K _____
 CRI ≥ 90 _____
 L90 / 50000 h _____
 initial MacAdam ≤ 3 SDCM _____
 R_g: 99 , R_r: 91 , R₍₁₋₁₅₎: 89 _____
 MR 0.54 _____
 MDER 0.49 _____

Optical

medium _____
 beam angle 25° _____
 PstLM ≤ 1.0 ¹ _____
 SVM ≤ 0.4 ¹ _____

Electrical

DALI-2 _____
 11.2 W _____
 PC2 220-240V _____
 57 lm/W _____
 1 DALI Addr. _____

Physical


rod 1500 mm _____
 diameter 47 mm _____
 height 110 mm _____
 0.61 kg _____

Cutout

diameter 65 mm _____
 min. ceiling thickness 9 mm _____
 max. ceiling thickness 25 mm _____
 recessed depth 130 mm _____

¹ Value of containing product at full load (undimmed)


Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	2780	0.44
2	690	0.89
3	310	1.33
4	170	1.78
5	110	2.22

Product drawing



Installation instructions



Lighting calculator

