

ARY rod suspended canopy surface

049-5221417M 005-2602197



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling | Suspended
 white | RAL 9016 ¹
 Canopy traffic white
 IP20
 642 lm
 fixture 76 lm/W ²

LED

2700 K
 CRI ≥ 90
 L90 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 99 | R_f: 91 | R₍₁₋₁₅₎: 89
 MR 0.54 | MDER 0.49

Optical

medium | beam angle 25°
 PstLM ≤ 1.0 ³ | SVM ≤ 0.4 ³

Electrical


Casambi
 PC2 | 220-240 V
 system 11.2 W | fixture 8.4 W
 18 Vf | 500 mA

Physical

rod 1500 mm with hook
 diameter 47 mm | height 110 mm

Decorative suspended luminaire in aluminium; surface white powder coated; height adjustable U-profile pendant rod suspension (white) 1500mm, feed 2000mm (1500mm in U-profile), incl. ceiling mounting ring + hook (white) for multiple positioning of the luminaire in the room; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2; 220-240 V; light source not replaceable; control gear replaceable by an authorized professional;


Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	2780	0.44
2	690	0.89
3	310	1.33
4	170	1.78
5	110	2.22

Product drawing



¹ RAL code

² incl. consideration of optical losses & internal control unit losses

³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

