

# ARY cable suspended

canopy trimless

049-5211417F 005-3511017 002-90733



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Suspended \_\_\_\_\_

white , RAL9016 <sup>1</sup> \_\_\_\_\_

Canopy traffic white \_\_\_\_\_

IP20 \_\_\_\_\_

688 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.54 \_\_\_\_\_

MDER 0.49 \_\_\_\_\_

## Optical

flood \_\_\_\_\_

beam angle 44° \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrical

DALI-2 \_\_\_\_\_

11.2 W \_\_\_\_\_

PC2 220-240V \_\_\_\_\_

61 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

## Physical

suspension 2000 mm with hook \_\_\_\_\_

diameter 47 mm \_\_\_\_\_

height 110 mm \_\_\_\_\_

0.56 kg \_\_\_\_\_

## Cutout

diameter 65 mm \_\_\_\_\_


min. ceiling thickness 9 mm \_\_\_\_\_

max. ceiling thickness 25 mm \_\_\_\_\_

recessed depth 130 mm \_\_\_\_\_

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)


## Light distribution



flood 44°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 1280     | 0.82  |
| 2     | 320      | 1.64  |
| 3     | 140      | 2.45  |
| 4     | 80       | 3.27  |
| 5     | 50       | 4.09  |

## Product drawing



## Installation instructions



## Lighting calculator



# ARY cable suspended

canopy trimless

049-5211417F 005-3511017 002-90733



Project / Type

Notes

Count / Date

## Maintenance Factors

| Operating Time [h] | 10 000                       | 20 000 | 30 000  | 40 000 | 50 000 |
|--------------------|------------------------------|--------|---|--------|--------|
| LLMF               | 0.97                         | 0.96   | 0.95  | 0.93   | 0.92   |
| LSF                | 1                            | 1      | 1   | 1      | 1      |
| MF                 | LMF × RSMF × LLMF × LSF      |        | RSMF <sup>a</sup> Room Surface Maintenance Factor |        |        |
| MF                 | Maintenance Factor           |        | LLMF Lamp Lumens Maintenance Factor               |        |        |
| LMF <sup>a</sup>   | Luminaire Maintenance Factor |        | LSF Lamp Survival Faktor                          |        |        |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10                            | 80                 |
| B13                            | 104                |
| B16                            | 130                |
| B20                            | 162                |
| C10                            | 135                |
| C13                            | 175                |
| C16                            | 220                |
| C20                            | 270                |

## Components

### MOUNTING SET trimless

|               |        |                   |
|---------------|--------|-------------------|
| COLOUR        | Ø (MM) | ARTICLE NUMBER(S) |
| traffic white | 75     | 005-3511017       |



### POWER SUPPLY

|            |                   |
|------------|-------------------|
| L·W·H (MM) | ARTICLE NUMBER(S) |
| 166·30·22  | 002-90733         |



## Mounting accessories

### RING CEILING MOUNTED

|               |        |                   |
|---------------|--------|-------------------|
| COLOUR        | Ø (MM) | ARTICLE NUMBER(S) |
| traffic white | 50     | 050-0510217       |
| jet black     | 50     | 050-0510218       |



## Optional electrical accessories

### DIN RAIL POWER SUPPLY

|            |                   |
|------------|-------------------|
| L·W·H (MM) | ARTICLE NUMBER(S) |
| 72·90·63   | 005-6520210       |



### DIN RAIL LED DRIVER

|                                |            |                   |
|--------------------------------|------------|-------------------|
| TYPE                           | L·W·H (MM) | ARTICLE NUMBER(S) |
| DALI-2   200-1050 mA   2 x 42W | 36·88·59   | 005-6121030       |



## Other accessories

### SPECIAL MOUNTING TOOL

|  |        |                   |
|--|--------|-------------------|
| TYPE   | Ø (MM) | ARTICLE NUMBER(S) |
| necessary to install mounting housing trimless | 100    | 063-8912110       |





Project / Type

Notes

Count / Date

Optical accessories

SHADE 300

| COLOUR           | Ø (MM) | ARTICLE NUMBER(S) |
|------------------|--------|-------------------|
| signal black     | 300    | 049-593311B       |
| velvet beige     | 300    | 049-593311C       |
| woodpecker olive | 300    | 049-593311G       |
| kingfisher grey  | 300    | 049-593311L       |
| madeira brown    | 300    | 049-593311T       |
| signal white     | 300    | 049-593311W       |



SHADE 400

| COLOUR           | Ø (MM) | ARTICLE NUMBER(S) |
|------------------|--------|-------------------|
| signal black     | 400    | 049-593411B       |
| velvet beige     | 400    | 049-593411C       |
| woodpecker olive | 400    | 049-593411G       |
| kingfisher grey  | 400    | 049-593411L       |
| madeira brown    | 400    | 049-593411T       |
| signal white     | 400    | 049-593411W       |



SHADE 500

| COLOUR           | Ø (MM) | ARTICLE NUMBER(S) |
|------------------|--------|-------------------|
| signal black     | 500    | 049-593511B       |
| velvet beige     | 500    | 049-593511C       |
| woodpecker olive | 500    | 049-593511G       |
| kingfisher grey  | 500    | 049-593511L       |
| madeira brown    | 500    | 049-593511T       |
| signal white     | 500    | 049-593511W       |

