

# ARY rod suspended canopy surface

049-5121617F 005-2601137



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Suspended \_\_\_\_\_  
 white , RAL9016 <sup>1</sup> \_\_\_\_\_  
 Canopy traffic white \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 791 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 L90 / 50000 h \_\_\_\_\_  
 initial MacAdam ≤ 3 SDCM \_\_\_\_\_  
 R<sub>g</sub>: 99 , R<sub>r</sub>: 89 , R<sub>(1-15)</sub>: 87 \_\_\_\_\_  
 MR 0.81 \_\_\_\_\_  
 MDER 0.73 \_\_\_\_\_

## Optical

flood \_\_\_\_\_  
 beam angle 44° \_\_\_\_\_

## Electrical


DALI-2 \_\_\_\_\_  
 11.2 W \_\_\_\_\_  
 PC2 220-240V \_\_\_\_\_  
 71 lm/W \_\_\_\_\_  
 1 DALI Addr. \_\_\_\_\_

## Physical

rod 1500 mm \_\_\_\_\_  
 diameter 47 mm \_\_\_\_\_  
 height 110 mm \_\_\_\_\_  
 0.45 kg \_\_\_\_\_

Decorative suspended luminaire in aluminium; surface white powder coated; height adjustable U-profile pendant rod suspension (white) 1500mm, feed in U-profile; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;


## Light distribution



flood 44°

h (m)	EO° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

## Product drawing



<sup>1</sup> RAL code

## Installation instructions



## Lighting calculator



# ARY rod suspended canopy surface

049-5121617F 005-2601137



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.97	0.96	0.95	0.93	0.92
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF RSMF<sup>a</sup> Room Surface Maintenance Factor  
 MF Maintenance Factor LLMF Lamp Lumens Maintenance Factor  
 LMF<sup>a</sup> Luminaire Maintenance Factor LSF Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Components

### CANOPY

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
500 mA   DALI-2	traffic white	115	005-2601137



### Mounting accessories

#### RING CEILING MOUNTED

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	50	050-0510217
jet black	50	050-0510218



### Optional electrical accessories

#### DIN RAIL POWER SUPPLY

L-W-H (MM)	ARTICLE NUMBER(S)
72-90-63	005-6520210



#### DIN RAIL LED DRIVER

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
DALI-2   200-1050 mA   2 x 42W	36-88-59	005-6121030



### Other accessories

#### SPECIAL MOUNTING TOOL

TYPE	Ø (MM)	ARTICLE NUMBER(S)
necessary to install mounting housing trimless	100	063-8912110



[049-5121617F 005-2601137] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

25.05.2024

2 / 2