

# ARY rod suspended canopy surface

049-512151XM 005-2601137



Project / Type \_\_\_\_\_  
 Notes \_\_\_\_\_  
 Count / Date \_\_\_\_\_



**General**  
 Ceiling , Suspended \_\_\_\_\_  
 special colours \_\_\_\_\_  
 Canopy traffic white \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 739 lm \_\_\_\_\_

**LED**  
 3000 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 L90 / 50000 h \_\_\_\_\_  
 initial MacAdam ≤ 3 SDCM \_\_\_\_\_  
 R<sub>g</sub>: 100 , R<sub>f</sub>: 90 , R<sub>(f-15)</sub>: 87 \_\_\_\_\_  
 MR 0.59 \_\_\_\_\_  
 MDER 0.54 \_\_\_\_\_


**Optical**  
 medium \_\_\_\_\_  
 beam angle 25° \_\_\_\_\_

**Electrical**  
 DALI-2 \_\_\_\_\_  
 11.2 W \_\_\_\_\_  
 PC2 220-240V \_\_\_\_\_  
 66 lm/W \_\_\_\_\_  
 1 DALI Addr. \_\_\_\_\_

**Physical**  
 rod 1500 mm \_\_\_\_\_  
 diameter 47 mm \_\_\_\_\_  
 height 110 mm \_\_\_\_\_  
 0.45 kg \_\_\_\_\_

Decorative suspended luminaire in aluminium; surface special colours powder coated; height adjustable U-profile pendant rod suspension (special colours) 1500mm, feed in U-profile; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;


## Light distribution



medium 25°

h (m)	EO° (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

## Product drawing



## Installation instructions



## Lighting calculator

