

# ARY adjustable rod suspended canopy surface

049-5131617F 005-2601137



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

tilt max 90°

rotation 265°

white , RAL9016 <sup>1</sup>

Canopy traffic white

IP20

791 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 89 , R<sub>(1-15)</sub>: 87

MR 0.81

MDER 0.73

Optical

flood

beam angle 44°

Electrical

DALI-2

11.2 W

PC2 220-240V

71 lm/W

1 DALI Addr.

Physical

rod 1500 mm


diameter 47 mm

height 110 mm

0.45 kg

<sup>1</sup> RAL code

## Light distribution



| flood 44° |          |       |  |
|-----------|----------|-------|--|
| h (m)     | E0° (lx) | ø (m) |  |
| 1         | 1470     | 0.82  |  |
| 2         | 370      | 1.64  |  |
| 3         | 160      | 2.45  |  |
| 4         | 90       | 3.27  |  |
| 5         | 60       | 4.09  |  |

## Product drawing



## Installation instructions

## Lighting calculator

