

# ARY cable suspended

canopy trimless

049-5111517F 005-3511017 002-90733



Project / Type

Notes

Count / Date



## General

Ceiling , Suspended

white , RAL9016 <sup>1</sup>

Canopy traffic white

IP20

791 lm

## LED

3000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 90 , R<sub>f(1-15)</sub>: 87

MR 0.59

MDER 0.54

## Optical

flood

beam angle 44°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2

11.2 W

PC2 220-240V

71 lm/W

1 DALI Addr.

## Physical

suspension 1500 mm

diameter 47 mm

height 110 mm

0.46 kg

## Cutout

diameter 65 mm


min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 130 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)


## Light distribution



flood 44°

h (m)	EO° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

## Product drawing



## Installation instructions



## Lighting calculator

