

ARY cable suspended

canopy trim

049-511141XM 005-3521017 002-90732



Project / Type
Notes
Count / Date



General

Ceiling , Suspended
special colours
Canopy traffic white
IP20
642 lm
fixture 76 lm/W ¹

LED

2700 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 99 , R _f : 91 , R ₍₁₋₁₅₎ : 89
MR 0.54
MDER 0.49

Optical

medium
beam angle 25°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical

non DIM
220-240 V
system 11.2 W
fixture 8.4 W
18 Vf
500 mA
PC2

Physical

suspension 1500 mm
diameter 47 mm
height 110 mm
0.48 kg

Cutout

diameter 65 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 70 mm

¹ incl. consideration of optical losses & internal control unit losses
² Value of containing product at full load (undimmed)

Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	2780	0.44
2	690	0.89
3	310	1.33
4	170	1.78
5	110	2.22

Product drawing



Installation instructions



Lighting calculator

