

SQUADRO 2 × 4 lamps wallwasher

trim

049-2040538B



Project / Type

Notes

Count / Date



General

Ceiling | Recessed

jet black | RAL 9005 ¹

IP20

10700 lm

LED

3000 K

CRI ≥ 80

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.58 | MDER 0.52

Optical

shelf / wall floor washer

PstLM ≤ 1.0^{2 3 4 5} | SVM ≤ 0.4^{2 3 4 5}

Electrical

DALI-2 | 2 DALI Addr.

PC2 | 220-240 V

system 86 W

system 124 lm/W ⁶

Physical

trim

length 290 mm | width 171 mm | height 78 mm

2.1 kg

Cutout


length 270 mm | width 152 mm

min. ceiling thickness 2 mm | max. ceiling thickness 25 mm


recessed depth 85 mm

Recessed ceiling spotlight in die cast aluminium with 2x4-lamp design; surface jet black powder coated; with wrap around edge; suitable for ceiling thickness of 2-25 mm; installation without tools using snap spring closure; heat sink integrated into luminaire geometry for optimum thermal management and passive cooling of LEDs; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; Aisle spotlight 1x shelf / 1x wall floor washer with special, multi-free-form, facet effect surface reflectors for high precision light control; precise shelf and aisle zone lighting, optimum longitudinal glare control for high viewing comfort in the aisle zone; adjustable light modules (tiltable +15° to -10°, maximum tilt range adjustable for one side); degree of protection IP20; IP 40 protection glass available as an accessory; accessories are listed separately; PC2; 220-240 V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² double-sided ³ single sided shelf floor
⁴ single sided wall floor
⁵ Value of containing product at full load (undimmed)
⁶ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator



SQUADRO 2 × 4 lamps wallwasher

trim
049-2040538B



Project / Type

Notes

Count / Date

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	10
B13	13
B16	16
B20	21
C1	16
C13	21
C16	26
C20	35

Optical accessories

IP40 PROTECTION GLASS

TYPE
2 x 4 lamps / single-sided

ARTICLE NUMBER(S)
049-2940010

