

048-36104177A



Ceiling , Surface
white , RAL9016/white <sup>1</sup>
Inner colour white
IP20
731 lm

2700 K
CRI $\geq 90$
L80 / 50000 h
initial MacAdam $\leq 3$ SDCM
R <sub>g</sub> : 97, R <sub>r</sub> : 91, R <sub>{f[1-15]}</sub> : 90
MR 0.53
MDER 0.48

wallwasher
PstLM $\leq 1.0$ <sup>2</sup>
SVM $\leq 0.4$ <sup>2</sup>

non DIM
9.7 W
PC1 220-240V
75 lm/W

length 72 mm  
width 72 mm  
height 108 mm  
0.5 kg

$$\begin{array}{r} 108 \\ \square 72 \end{array}$$



# SASSO 60 square wallwasher

ceiling  
048-36104177A



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.89	0.85	0.82
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	62
B13	81
B16	98
B20	124
C10	104
C13	137
C16	168
C20	209

