

048-36104119A



Ceiling , Surface
black , RAL9005/gold ¹
Inner colour gold
IP20
691 lm

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 97, R _r : 91, R _{f[1-5]} : 90
MR 0.53
MDER 0.48

wallwasher
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

non DIM
9.7 W
PC1 220-240V
71 lm/W

length 72 mm
width 72 mm
height 108 mm
0.5 kg



SASSO 60 square wallwasher

ceiling
048-36104119A



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.89	0.85	0.82
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	62
B13	81
B16	98
B20	124
C10	104
C13	137
C16	168
C20	209

