

SASSO 60 round wallwasher

semi-recessed
048-37016174A 002-90762



Project / Type

Notes

Count / Date



General
Ceiling , Semi-Recessed
rotation 360°
white , RAL9016/matt silver ¹
Inner colour matt silver
IP20
766 lm

LED
4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 94 , R _f : 87 , R _{f(1-15)} : 86
MR 0.8
MDER 0.72

Optical
wallwasher
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²


Electrical
DALI-2
9.7 W
PC2 220-240V
79 lm/W

Physical
diameter 72 mm
height 75 mm
0.12 kg

Cutout
recessed depth 120 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator



SASSO 60 round wallwasher

semi-recessed
048-37016174A 002-90762



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.89	0.85	0.82
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	18
B16	30
C10	23
C16	36

Components

CONVERTER

L-W-H (MM)	ARTICLE NUMBER(S)
143-43-30	002-90762



Optional electrical accessories

DIN RAIL POWER SUPPLY

L-W-H (MM)	ARTICLE NUMBER(S)
72-90-63	005-6520210



DIN RAIL LED DRIVER

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
DALI-2 200-1050 mA 2 x 42W	36-88-59	005-6121030

