

SASSO 60 round wallwasher

semi-recessed
048-37016114A 002-90771



Project / Type

Notes

Count / Date



General
Ceiling , Semi-Recessed
rotation 360°
black , RAL9005/matt silver ¹
Inner colour matt silver
IP20
766 lm

LED
4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 94 , R _f : 87 , R _{f(1-15)} : 86
MR 0.8
MDER 0.72

Optical
wallwasher
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²


Electrical
non DIM
9.7 W
PC2 220-240V
79 lm/W

Physical
diameter 72 mm
height 75 mm
0.06 kg


Cutout
recessed depth 85 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator



[*048-37016114A 002-90771*] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com