

SASSO 60 square wallwasher

ceiling
048-36105319A



Project / Type

Notes

Count / Date



General
Ceiling , Surface
black , RAL9005/gold ¹
Inner colour gold
IP20
746 lm

LED
3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 97 , R _f : 91 , R _{f(1-15)} : 89
MR 0.6
MDER 0.54


Optical
wallwasher
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical
DALI-2
9.7 W
PC1 220-240V
77 lm/W

Physical
length 72 mm
width 72 mm
height 108 mm
0.5 kg

Square ceiling mounted spotlight made of aluminium; surface black (housing/light inset); luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); converter integrated into spotlight head; luminaire for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

