

SASSO 60 round adjustable  
ceiling  
048-31106374S



Project / Type

Notes

Count / Date



Cylindrical surface mounted spotlight in die-cast aluminium; suitable for ceiling mounting; surface white (housing/light inset); 360° rotatable and 30° tiltable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 12° beam; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); converter integrated into spotlight head; luminaire for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



**General**

Ceiling , Surface

tilt max 30°

rotation 360°

white , RAL9016/matt silver <sup>1</sup>

Inner colour matt silver

IP20

555 lm

**LED**

4000 K

CRI ≥ 90

initial MacAdam ≤ 3 SDCM

**Optical**

spot

beam angle 12°

UGR < 16 , ≥65° <1500 cd/m²

**Electrical**

DALI-2

10.7 W

PC1 220-240V

52 lm/W

1 DALI Addr.


**Physical**

diameter 72 mm

height 108 mm

0.5 kg

Light distribution



Product drawing



<sup>1</sup> RAL code

Installation instructions



Lighting calculator

