

SASSO 60 round adjustable

ceiling

048-31106177S



Project / Type

Notes

Count / Date



General
Ceiling , Surface
tilt max 30°
rotation 360°
white , RAL9016/white ¹
Inner colour white
IP20
528 lm

LED
4000 K
CRI ≥ 90
initial MacAdam ≤ 3 SDCM


Optical
spot
beam angle 11°
UGR < 19
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical
non DIM
10.7 W
PC1 220-240V
49 lm/W

Physical
diameter 72 mm
height 108 mm
0.5 kg

Cylindrical surface mounted spotlight in die-cast aluminium; suitable for ceiling mounting; surface white (housing/light inset); 360° rotatable and 30° tiltable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 11° beam; UGR ≤ 19; degree of protection IP20; PC1 220-240V; incl. converter, non dimmable; converter integrated into spotlight head; luminaire for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

