

SASSO 60 round adjustable ceiling 048-31104379F



Project / Type _____

Notes _____

Count / Date _____



| |
|-----------------------------------|
| General |
| Ceiling , Surface |
| tilt max 30° |
| rotation 360° |
| white , RAL9016/gold ¹ |
| Inner colour gold |
| IP20 |
| 762 lm |

| |
|---|
| LED |
| 2700 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 99 , R _r : 91 , R _{t(1-15)} : 89 |
| MR 0.53 |
| MDER 0.48 |

| |
|-----------------------------|
| Optical |
| flood |
| beam angle 39° |
| UGR < 16 , ≥65° <3000 cd/m² |


Cylindrical surface mounted spotlight in die-cast aluminium; suitable for ceiling mounting; surface white (housing/light inset); 360° rotatable and 30° tiltable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 39° beam; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); converter integrated into spotlight head; luminaire for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

| |
|--------------|
| Electrical |
| DALI-2 |
| 10.4 W |
| PC1 220-240V |
| 73 lm/W |
| 1 DALI Addr. |

| |
|----------------|
| Physical |
| diameter 72 mm |
| height 108 mm |
| 0.5 kg |

¹ RAL code

Light distribution



Product drawing



Installation instructions



Lighting calculator

