

SASSO 60 round adjustable

ceiling

048-31104374S



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Surface _____

tilt max 30° _____

rotation 360° _____

white , RAL9016/matt silver ¹ _____

Inner colour matt silver _____

IP20 _____

495 lm _____

LED

2700 K _____

CRI ≥ 90 _____

initial MacAdam ≤ 2 SDCM _____

R_g: 99 , R_f: 91 , R₍₁₋₁₅₎: 89 _____

MR 0.53 _____

MDER 0.48 _____

Optical

spot _____

beam angle 12° _____

UGR < 16 , ≥65° <1500 cd/m² _____

Electrical

DALI-2 _____

10.7 W _____

PC1 220-240V _____

46 lm/W _____

1 DALI Addr. _____

Physical


diameter 72 mm _____

height 108 mm _____


0.5 kg _____

Cylindrical surface mounted spotlight in die-cast aluminium; suitable for ceiling mounting; surface white (housing/light inset); 360° rotatable and 30° tiltable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 12° beam; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); converter integrated into spotlight head; luminaire for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code

Installation instructions



Lighting calculator

