

SASSO 60 round adjustable ceiling 048-31104371S



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



**General**

Ceiling , Surface \_\_\_\_\_

tilt max 30° \_\_\_\_\_

rotation 360° \_\_\_\_\_

white , RAL9016/black <sup>1</sup> \_\_\_\_\_

Inner colour black \_\_\_\_\_

IP20 \_\_\_\_\_

386 lm \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

initial MacAdam ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.53 \_\_\_\_\_

MDER 0.48 \_\_\_\_\_

**Optical**

spot \_\_\_\_\_

beam angle 12° \_\_\_\_\_

UGR < 13 \_\_\_\_\_

**Electrical**

DALI-2 \_\_\_\_\_

10.7 W \_\_\_\_\_

PC1 220-240V \_\_\_\_\_

36 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

**Physical**


diameter 72 mm \_\_\_\_\_

height 108 mm \_\_\_\_\_

0.5 kg \_\_\_\_\_

<sup>1</sup> RAL code

Light distribution



Product drawing



Installation instructions



Lighting calculator



SASSO 60 round  
adjustable  
ceiling  
048-31104371S



Project / Type

Notes

Count / Date

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10                            | 40                 |
| B13                            | 50                 |
| B16                            | 65                 |
| B20                            | 85                 |
| C10                            | 70                 |
| C13                            | 80                 |
| C16                            | 104                |
| C20                            | 130                |

