

SASSO 60 square downlight

ceiling
048-30104371S



Project / Type


Notes

Count / Date



Square ceiling mounted spotlight made of aluminium; surface white (housing/light inset); luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 12° beam; UGR ≤ 13 ; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); converter integrated into spotlight head; luminaire for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Surface

white , RAL9016/black ¹

Inner colour black

IP20

406 lm

LED

2700 K

CRI ≥ 90

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_f: 91 , R_{f(1-15)}: 89

MR 0.53

MDER 0.48

Optical

spot

beam angle 12°

UGR < 13

Electrical

DALI-2

10.7 W

PC1 220-240V

38 lm/W

1 DALI Addr.

Physical

length 72 mm

width 72 mm

height 108 mm

0.5 kg

¹ RAL code

Installation instructions



Lighting calculator

