

SASSO 60 round  
adjustable  
ceiling  
048-31104171S



Project / Type

Notes

Count / Date



|                                    |
|------------------------------------|
| General                            |
| Ceiling , Surface                  |
| tilt max 30°                       |
| rotation 360°                      |
| white , RAL9016/black <sup>1</sup> |
| Inner colour black                 |
| IP20                               |
| 386 lm                             |

|  |
|--|
| LED  |
| 2700 K   |
| CRI ≥ 90   |
| initial MacAdam ≤ 2 SDCM   |
| R <sub>g</sub> : 99 , R <sub>f</sub> : 91 , R <sub>(1-15)</sub> : 89 |
| MR 0.53  |
| MDER 0.48  |


|                          |
|--------------------------|
| Optical                  |
| spot                     |
| beam angle 12°           |
| UGR < 13                 |
| PstLM ≤ 1.0 <sup>2</sup> |
| SVM ≤ 0.4 <sup>2</sup>   |

|              |
|--------------|
| Electrical   |
| non DIM      |
| 10.7 W       |
| PC1 220-240V |
| 36 lm/W      |

|                |
|----------------|
| Physical       |
| diameter 72 mm |
| height 108 mm  |
| 0.5 kg         |

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator

