

SASSO 60 round adjustable

semi-recessed
048-31015111S 002-90762



Project / Type

Notes

Count / Date



General
Ceiling , Semi-Recessed
tilt max 30°
rotation 360°
black , RAL9005/black ¹
Inner colour black
IP20
468 lm

LED
3000 K
CRI ≥ 90
initial MacAdam ≤ 3 SDCM

Optical
spot
beam angle 12°
UGR < 13
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical
DALI-2
13.1 W
PC2 220-240V
36 lm/W
1 DALI Addr.


Physical
diameter 72 mm
height 75 mm
0.12 kg

Cutout
recessed depth 120 mm


¹ RAL code ² Value of containing product at full load (undimmed)

Cylindrical semi-recessed spotlight made of aluminium; surface black (housing/light inset); 360° rotatable and 30° tiltable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 12° beam; UGR ≤ 13; degree of protection IP20; PC2 220-240V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

