

SASSO 60 square downlight

semi-recessed

048-30014111S 002-90762



Project / Type

Notes

Count / Date



General

Ceiling , Semi-Recessed
black , RAL9005/black ¹
Inner colour black
front IP40 , back IP20
464 lm

LED

2700 K
CRI ≥ 90
initial MacAdam ≤ 3 SDCM
R_g: 99 , R_f: 91 , R₍₁₋₁₅₎: 89
MR 0.53
MDER 0.48

Optical

spot
beam angle 12°
UGR < 13
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical

DALI-2
13.1 W
PC2 220-240V
35 lm/W
1 DALI Addr.

Physical


length 72 mm
width 72 mm
height 75 mm
0.12 kg

Cutout


recessed depth 120 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator



SASSO 60 square
downlight

semi-recessed

048-30014111S 002-90762



Project / Type

Notes

Count / Date

Components

CONVERTER

L·W·H (MM)	ARTICLE NUMBER(S)
143-43-30	002-90762



Optional electrical accessories

DIN RAIL POWER SUPPLY

L·W·H (MM)	ARTICLE NUMBER(S)
72-90-63	005-6520210



DIN RAIL LED DRIVER

TYPE	L·W·H (MM)	ARTICLE NUMBER(S)
DALI-2 200-1050 mA 2 x 42W	36-88-59	005-6121030



Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	18
B16	30
C10	23
C16	36

