

SASSO 40 round adjustable

trim

048-2820614F 048-2896318 002-90744



Project / Type

Notes

Count / Date



↑ IP20

↓ IP40

220-240V

360°

X-PERT

X-PERT

General

Ceiling , Recessed

tilt max 30°

rotation 360°

matt silver

Mounting set jet black

front IP40 , back IP20

516 lm

LED

4000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

Optical

flood

beam angle 44°

UGR < 19

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

non DIM

9.9 W

PC2 220-240V

52 lm/W

Physical

trim

diameter 60 mm

height 50 mm

0.49 kg

Cutout

diameter 56 mm

min. ceiling thickness 2 mm


max. ceiling thickness 25 mm

recessed depth 60 mm

¹ Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; surface matt silver; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 44° beam; UGR ≤ 19; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

