

# SASSO 100 square adjustable

trim 2 lamps

048-2730611F 048-2799317 002-90779



Project / Type

Notes

Count / Date



↑ IP20  
↓ IP40

220-240V

General
Ceiling , Recessed
tilt max 30°
black , RAL9005 <sup>1</sup>
Mounting set traffic white
front IP40 , back IP20
3360 lm


LED
4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 97 , R <sub>f</sub> : 90 , R <sub>(1-5)</sub> : 89
MR 0.81
MDER 0.74

Optical
flood
beam angle 45°
UGR < 16 , ≥65° <1500 cd/m <sup>2</sup>
P <sub>st</sub> LM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>


Recessed square spotlight in die-cast aluminium; 2 lamps; surface black; 30° tiltable; installation without tools in mounting set due to patented ball catch system; rectangular installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 45° beam; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m<sup>2</sup>; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical
DALI-2
40 W
total insets 34 W
PC2 220-240V
84 lm/W
1 DALI Addr.

## Light distribution



## Product drawing



Physical
trim
length 218 mm
width 118 mm
height 95 mm
0.6 kg

Cutout
length 210 mm
width 112 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 100 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

