

SASSO 100 round adjustable

trim 2 lamps

048-2720617W 048-279831G 002-90776



Project / Type
Notes
Count / Date



↑ IP20 ↓ IP40	220-240V	360° rotation	X-PERT	X-PERT
------------------	----------	---------------	--------	--------

General

Ceiling , Recessed
tilt max 30°
rotation 360°
white , RAL9016 ¹
Mounting set silver-grey
front IP40 , back IP20
4780 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 97 , R _r : 90 , R ₍₁₋₁₅₎ : 89
MR 0.81
MDER 0.74

Optical

wide flood
beam angle 59°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical

DALI-2
58 W
total insets 50 W
PC2 220-240V
82 lm/W
1 DALI Addr.

Physical


trim
length 218 mm
width 118 mm
height 95 mm
0.59 kg

Cutout


diameter 105 mm
length 205 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 100 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator

