

# SASSO 100 round adjustable

trim

048-2720417S 048-2796318 002-90774



Project / Type	
Notes	
Count / Date	



↑ IP20 ↓ IP40	220-240V	360° rotation	X-PERT	X-PERT
------------------	----------	---------------	--------	--------

## General

Ceiling , Recessed
tilt max 30°
rotation 360°
white , RAL9016 <sup>1</sup>
Mounting set jet black
front IP40 , back IP20
1860 lm

## LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>r</sub> : 91 , R <sub>(1-15)</sub> : 89
MR 0.53
MDER 0.48

## Optical

spot
beam angle 19°
UGR < 19
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Electrical

non DIM
29.2 W
PC2 220-240V
64 lm/W

## Physical


trim
diameter 118 mm
height 95 mm
0.44 kg

## Cutout


diameter 108 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 100 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

