

SASSO 100 round adjustable

trim

048-2720511W 048-2796318 002-90776




| |
|----------------|
| Project / Type |
| Notes |
| Count / Date |



Round recessed spotlight in die-cast aluminium; 1 lamp; surface black; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 60° beam; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

| |
|------------------------------|
| Ceiling , Recessed |
| tilt max 30° |
| rotation 360° |
| black , RAL9005 ¹ |
| Mounting set jet black |
| front IP40 , back IP20 |
| 2160 lm |

LED

| |
|---|
| 3000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 100 , R _f : 91 , R _{f(1-5)} : 88 |
| MR 0.59 |
| MDER 0.53 |

Optical

| |
|---------------------------------------|
| wide flood |
| beam angle 60° |
| $\geq 65^\circ < 3000 \text{ cd/m}^2$ |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Electrical

| |
|--------------|
| DALI-2 |
| 29.2 W |
| PC2 220-240V |
| 74 lm/W |
| 1 DALI Addr. |

Physical

| |
|-----------------|
| trim |
| diameter 118 mm |
| height 95 mm |
| 0.48 kg |

Cutout

| |
|------------------------------|
| diameter 108 mm |
| min. ceiling thickness 2 mm |
| max. ceiling thickness 25 mm |
| recessed depth 100 mm |

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

