

SASSO 100 round adjustable

trimless exposed concrete

048-2720414M 048-2795210 002-90776



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Recessed
 tilt max 30°
 rotation 360°
 matt silver
 front IP40 , back IP20
 1850 lm

LED

2700 K
 CRI ≥ 90
 L80 / 50000 h
 initial MacAdam ≤ 2 SDCM
 R_g: 99 , R_f: 91 , R₍₁₋₁₅₎: 89
 MR 0.53
 MDER 0.48

Optical

medium
 beam angle 32°
 UGR < 16 , ≥65° <3000 cd/m²
 P_{stLM} ≤ 1.0¹
 SVM ≤ 0.4¹

Electrical

DALI-2
 29.2 W
 PC2 220-240V
 63 lm/W
 1 DALI Addr.

Physical

trimless
 length 230 mm
 width 230 mm
 height 162 mm
 2.61 kg


Cutout

recessed depth 100 mm


¹ Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; concrete housings for exposed concrete ceilings; for trimless installation; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 32° beam; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

