

# SASSO 100 round adjustable

trimless exposed concrete

048-2720411S 048-2795210 002-90777



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



↑ IP20  
↓ IP40

220-240V

360° rotation

X-PERT

X-PERT

**General**

Ceiling , Recessed

tilt max 30°

rotation 360°

black , RAL9005 <sup>1</sup>

front IP40 , back IP20

1330 lm

**LED**

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.53

MDER 0.48

**Optical**

spot

beam angle 19°

UGR < 13 , ≥65° <3000 cd/m<sup>2</sup>

P<sub>st</sub>LM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

**Electrical**

non DIM

20.2 W

PC2 220-240V

66 lm/W

**Physical**

trimless

length 230 mm

width 230 mm

height 162 mm


2.59 kg

**Cutout**


recessed depth 100 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

