

# SASSO 100 square downlight

trim 2 lamps

048-2710414S 048-2799318 002-90777



Project / Type	
Notes	
Count / Date	



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

## General

Ceiling , Recessed
matt silver
Mounting set jet black
front IP44 , back IP20
2840 lm

## LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>r</sub> : 91 , R <sub>t(1-15)</sub> : 89
MR 0.53
MDER 0.48

## Optical

spot
beam angle 20°
UGR < 13 , ≥65° <3000 cd/m <sup>2</sup>
PstLM ≤ 1.0 <sup>1</sup>
SVM ≤ 0.4 <sup>1</sup>

## Electrical

non DIM
40 W
total insets 34 W
PC2 220-240V
71 lm/W

## Physical


trim
length 218 mm
width 118 mm
height 75 mm
0.6 kg

## Cutout

length 210 mm
width 112 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 100 mm

<sup>1</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

