

SASSO 100 round downlight

trim 2 lamps

048-2700614S 048-279831G 002-90776



Project / Type

Notes

Count / Date



General

Ceiling , Recessed

matt silver

Mounting set silver-grey

front IP44 , back IP20

4100 lm

LED

4000 K

CRI \geq 90

L80 / 50000 h

initial MacAdam \leq 2 SDCM

R_g: 97 , R_r: 90 , R_{t(1-15)}: 89

MR 0.81

MDER 0.74

Optical

spot

beam angle 19°

UGR < 13

PstLM \leq 1.0 ¹

SVM \leq 0.4 ¹

Electrical

DALI-2

58 W

total insets 50 W

PC2 220-240V

71 lm/W

1 DALI Addr.

Physical

trim

length 218 mm

width 118 mm

height 75 mm

0.59 kg

Cutout

diameter 105 mm

length 205 mm


min. ceiling thickness 2 mm

max. ceiling thickness 25 mm


recessed depth 100 mm

¹ Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator



[048-2700614S 048-279831G 002-90776] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

29.05.2024

1 / 1