

SASSO 60 square wallwasher/floor

trim 2 lamps


048-2651617W 048-2699317 002-90771



Project / Type

Notes

Count / Date



General

Ceiling , Recessed
 white , RAL9016 ¹
 Mounting set traffic white
 IP20
 1630 lm

LED

4000 K
 CRI ≥ 90
 L80 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 94 , R_r: 87 , R_{r(1-15)}: 86
 MR 0.8
 MDER 0.72

Optical

wallwasher floor
 P_{stLM} ≤ 1.0 ²
 SVM ≤ 0.4 ²

Electrical

non DIM
 19.4 W
 total insets 16.5 W
 PC2 220-240V
 84 lm/W

Physical


trim
 length 147 mm
 width 81 mm
 height 49 mm
 0.28 kg

Cutout


length 138 mm
 width 73 mm
 min. ceiling thickness 2 mm
 max. ceiling thickness 25 mm
 recessed depth 90 mm

Recessed square spotlight in die-cast aluminium; 2 lamps; surface white; installation without tools in mounting set due to patented ball catch system; rectangular installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2 220-240V; incl. converter, non dimmable; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

