

SASSO 60 emergency light

trim

048-2693231 048-2696318



Project / Type
Notes
Count / Date



General

Ceiling , Recessed
rotation 360°
black , RAL9005 ¹
Mounting set jet black
IP20
206 ² , 208 ³ , 217 ⁴ lm

LED

4000 K
CRI ≥ 80

Optical

emergency spot ² , emergency escape route ³ , emergency anti panic ⁴
beam angle 21° ² , 103°x25° ³ , 149°x150° ⁴

Electrical




1.0 W
PC2 220-240V
206 ² , 208 ³ , 217 ⁴ lm/W

Physical



trim
diameter 80 mm
height 94 mm
0.3 kg

Round LED emergency light inset; surface lacquered in black; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; incl. 3 interchangeable lenses: anti panic / escape route / spot; incl. 3h rechargeable battery; Pro DALI with monitoring via DALI; light colour 4000 K; CRI ≥ 80; degree of protection IP20; PC2 220-240V; light source not replaceable;

Light distribution



Product drawing



Cutout

diameter 73 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 110 mm

¹ RAL code ² Spot lens ³ Escape route lens ⁴ Anti panic lens

Installation instructions



Lighting calculator



[048-2693231 048-2696318] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

16.05.2024