

SASSO 60 emergency light pro

trimless exposed concrete
048-2693231 048-2695210



Project / Type

Notes

Count / Date



Round LED emergency light inset; surface lacquered in black; 360° rotatable; installation without tools in mounting set due to patented ball catch system; concrete housings for exposed concrete ceilings; for trimless installation; incl. 3 interchangeable lenses: anti panic / escape route / spot; incl. 3h rechargeable battery; Pro DALI with monitoring via DALI; light colour 4000 K; CRI ≥ 80; degree of protection IP20; PC2 220-240V; light source not replaceable;



General

Ceiling , Recessed

rotation 360°

black , RAL9005 ¹

IP20

206², 208³, 217⁴ lm

LED

4000 K

CRI ≥ 80

Optical

emergency spot², emergency escape route³,
emergency anti panic⁴

beam angle 21°², 103°x25°³, 149°x150°⁴

Electrical

1.0 W

PC2 220-240V

206², 208³, 217⁴ lm/W

Physical

trimless


length 230 mm

width 230 mm


height 162 mm

2.45 kg

Light distribution



Product drawing



Cutout

recessed depth 110 mm

¹ RAL code ² Spot lens ³ Escape route lens ⁴ Anti panic lens

Installation instructions



Lighting calculator

