

# SASSO 60 emergency light selftest

trim  
048-2693221 048-2696318



Project / Type

Notes

Count / Date



General

Ceiling , Recessed

rotation 360°

black , RAL9005 <sup>1</sup>

Mounting set jet black

IP20

206<sup>2</sup>, 208<sup>3</sup>, 217<sup>4</sup> lm

LED

4000 K

CRI ≥ 80

Optical

emergency spot<sup>2</sup>, emergency escape route<sup>3</sup>, emergency anti panic<sup>4</sup>

beam angle 21°<sup>2</sup>, 103°x25°<sup>3</sup>, 149°x150°<sup>4</sup>

Electrical

1.0 W

PC2 220-240V

206<sup>2</sup>, 208<sup>3</sup>, 217<sup>4</sup> lm/W

Physical

trim




diameter 80 mm

height 94 mm



0.04 kg

Round LED emergency light inset; surface lacquered in black; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; incl. 3 interchangeable lenses: anti panic / escape route / spot; incl. 3h rechargeable battery; selftest with status LED; light colour 4000 K; CRI ≥ 80; degree of protection IP20; PC2 220-240V; light source not replaceable;

## Light distribution



## Product drawing



Cutout

diameter 73 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 110 mm

<sup>1</sup> RAL code <sup>2</sup> Spot lens <sup>3</sup> Escape route lens <sup>4</sup> Anti panic lens

Installation instructions

Lighting calculator



# SASSO 60 emergency light selftest

trim  
048-2693221 048-2696318



Project / Type

Notes

Count / Date

## Components

### MOUNTING SET with trim 1 lamp

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
for intermediate ceilings	jet black	80	048-2696318



## Mounting accessories

### PRIMED CONCRETE MOUNTING HOUSING

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
white aluminium	614-307-120	048-2695110



## Electrical accessories

### REPLACEMENT ACCUPACK

TYPE	ARTICLE NUMBER(S)
3h battery life	048-2693910

