

SASSO 60 emergency light selftest

trim

048-2693221 048-2696318



Project / Type


Notes

Count / Date



Round LED emergency light inset; surface lacquered in jet black; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; incl. 3 interchangeable lenses: anti panic / escape route / spot; incl. 3h rechargeable battery; selftest with status LED; light colour 6500 K; CRI ≥ 80; degree of protection IP20; PC2; light source not replaceable;

Product drawing



General

Ceiling | Recessed

rotation 360°

jet black | RAL 9005

Mounting set jet black

IP20

206¹, 208², 217³ lm

LED

6500 K

CRI ≥ 80

Optical

emergency light

Electrical

PC2 | 220-240 V

system 1.0 W

Physical

trim

diameter 80 mm | height 94 mm

0.35 kg

Cutout

diameter 73 mm

min. ceiling thickness 2 mm | max. ceiling thickness 25 mm

recessed depth 110 mm

¹ Spot lens ² Escape route lens ³ Anti panic lens

Installation instructions



SASSO 60 emergency light selftest

trim

048-2693221 048-2696318



Project / Type


Notes

Count / Date

Components

MOUNTING SET with trim 1 lamp


TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
for intermediate ceilings	jet black	80	048-2696318



Mounting accessories

PRIMED CONCRETE MOUNTING HOUSING

L·W·H (MM)	ARTICLE NUMBER(S)
614·307·120	048-2695110



Electrical accessories

REPLACEMENT ACCUPACK

TYPE	ARTICLE NUMBER(S)
3h battery life	048-2693910

