

SASSO 60 emergency light selftest

trimless

048-2693221 048-2696117



Project / Type

Notes

Count / Date



General

Ceiling , Recessed

rotation 360°

black , RAL9005 ¹

Mounting set traffic white

IP20

206², 208³, 217⁴ lm

LED

4000 K

CRI ≥ 80

Optical

emergency spot², emergency escape route³, emergency anti panic⁴

beam angle 21°², 103°x25°³, 149°x150°⁴

Electrical

1.0 W

PC2 220-240V

206², 208³, 217⁴ lm/W

Physical

trimless


diameter 73 mm

height 94 mm


0.06 kg

Round LED emergency light inset; surface lacquered in black; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 12.5/15/25 mm; with trim traffic white; incl. 3 interchangeable lenses: anti panic / escape route / spot; incl. 3h rechargeable battery; selftest with status LED; light colour 4000 K; CRI ≥ 80; degree of protection IP20; PC2 220-240V; light source not replaceable;

Light distribution



Product drawing



Cutout

diameter 73 mm

recessed depth 110 mm

¹ RAL code ² Spot lens ³ Escape route lens ⁴ Anti panic lens

Installation instructions



Lighting calculator



[“048-2693221 048-2696117”] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com