

SASSO 60 emergency light basic

trim

048-2693217 048-2696317



Project / Type

Notes

Count / Date



General

Ceiling , Recessed

rotation 360°

white , RAL9016 ¹

Mounting set traffic white

IP20

206², 208³, 217⁴ lm

LED

4000 K

CRI ≥ 80

Optical

emergency spot², emergency escape route³, emergency anti panic⁴

beam angle 21°², 103°x25°³, 149°x150°⁴

Electrical

1.0 W

PC2 220-240V

206², 208³, 217⁴ lm/W

Physical

trim




diameter 80 mm

height 94 mm



0.27 kg

Round LED emergency light inset; surface lacquered in white; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; incl. 3 interchangeable lenses: anti panic / escape route / spot; incl. 3h rechargeable battery; with test button; light colour 4000 K; CRI ≥ 80; degree of protection IP20; PC2 220-240V; light source not replaceable;

Light distribution



Product drawing



Cutout

diameter 73 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 110 mm

¹ RAL code ² Spot lens ³ Escape route lens ⁴ Anti panic lens

Installation instructions



Lighting calculator

