

SASSO 60 round wallwasher

trim 2 lamps

048-2641517A 048-2698318 002-90771



Project / Type _____
 Notes _____
 Count / Date _____



General

Ceiling , Recessed _____
 rotation 360° _____
 white , RAL9016 ¹ _____
 Mounting set jet black _____
 IP20 _____
 1530 lm _____

LED

3000 K _____
 CRI ≥ 90 _____
 L80 / 50000 h _____
 initial MacAdam ≤ 3 SDCM _____
 R_g: 97 , R_f: 91 , R₍₁₋₁₅₎: 89 _____
 MR 0.6 _____
 MDER 0.54 _____

Optical

wallwasher _____
 PstLM ≤ 1.0 ² _____
 SVM ≤ 0.4 ² _____

Electrical

non DIM _____
 19.4 W _____
 total insets 16.5 W _____
 PC2 220-240V _____
 79 lm/W _____

Physical

trim _____
 length 147 mm _____
 width 80 mm _____
 height 48 mm _____
 0.28 kg _____


Cutout

diameter 70 mm _____
 length 136 mm _____
 min. ceiling thickness 2 mm _____
 max. ceiling thickness 25 mm _____
 recessed depth 90 mm _____


¹ RAL code ² Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 2 lamps; surface white; 360° rotatable; installation without tools in mounting set due to patented ball catch system; oval installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2 220-240V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

